

Sterile Autoclavable Container for Nisco Encapsulation unit VARV1



Nisco Engineering AG

Wehntalerstrasse 562
CH-8046 Zurich, Switzerland


Tel: +41 44 380 06 30

Fax: +41 44 380 06 31

e-mail: mailbox@nisco.ch

<http://www.nisco.ch>

Sterile container is designed for encapsulation with max. three nozzles at the same time. It is the ideal tool if you have to produce beads on high level pharmaceutical or medical standard. It is delivered with the required material certificates to ease the validation of your process.



Legend:


- | | |
|--|---|
| 1 Product feed to max. 3 nozzles two blinds are supplied if you want to work with one nozzle only. | 7 Nozzle standard or special nozzles as per Nisco's Standard |
| 2 Air inlet to decrease humidity (to prevent short circuit) with 0.2µm filter | 8 Electrode to compensate the increasing surface of the hardening solution. |
| 3 Vent to decrease humidity (to prevent short circuit) with 0.2µm filter | 9 Autoclavable Glass vessel (process is visible from outside) |
| 4 Clamp cover on earth | 10 Hardening solution with the beads |
| 5 Hose connection for nozzle | 11 Agitation element for stirring |
| 6 Electrode on high voltage with isolation | |

Aeration:

When you produce drops in a closed container with a watery solution, the humidity within the container gradually increases, which, after a while, will lead to sparking and short circuits. To overcome the problem, we recommend supplying the container with dry air. The air inlet and outlet can be equipped with a standard autoclavable sterile filter of 0,2µm. Two sample filters are in the scope of supply.

Process Information:

The Nisco electrostatic accelerator (see the schema left) allows the size of the beads to be independent of the level of the hardening solution, which gradually rises by adding polymer drops.



Materials in contact with product

All materials are supplied with material certificates:

Stainless steel parts:	1.4435 or equivalent
Electrode:	titanium
Isolation parts:	PEEK
Nozzles:	1.4435 or equivalent
Gaskets:	EPDM or silicone depending on application
Glass cylinder:	borosilicate
O-Rings:	EPDM or silicone depending on application
Hoses:	silicone or polypropylene

Materials without contact to product

Stainless steel parts:	1.4301 or equivalent
------------------------	----------------------